

Latex Printer Settings

Profiles Available:

L25500 Printers:	L26500, L28500 Printers:	LX820, LX850 and HP Printers with 610 Inks:
		

All profiles are available for download at: www.fishertextiles.com/profiles.php

L25500 Printers

RIP: Caldera
Load as: Fabric
Print Mode: 10 passes bidi
InkLimit: Normal
Drying temperature: 50°C
Curing temperature: 100°C
Airflow: 30%
OMAS: Enable
Cutter: Disable
Tension: 15N/m
Vaccum: 5mmH20
WUDTO: 5°C
WUCTO: 0°C
CDDTO: 0°C
CDCTO: 0°C
Pmin: 1kW



L26500, L28500 Printers:

RIP: Onyx10
Load as: Fabric
Print Mode: 16 passes bidir 40 ips
InkLimit: High
Drying temperature: 55°C
Curing temperature: 100°C
Airflow: 30%
OMAS: Enable
Cutter: Disable
Tension: 15N/m
Vaccum: 5mmH20
WUDTO: 5°C
WUCTO: 0°C
CDDTO: 0°C
CDCTO: 0°C
Pmin: 0,7kW



LX820, LX850 and HP Printers with 610 Inks

RIP: Onyx and Caldera
Load as: [Fabric] Polyester Fabric - 150%
Print Mode: 10 passes bidi
Input Tension: 75N/m
Output Tension: 60N/m
Vacuum: 15mmH20
Airflow: 50%
Drying Temperature: 60°C
Curing Temperature: 95°C

