







Latex Printer Settings

Profiles Available:

L25500 Printers:	L26500, L28500 Printers:	L65500, LX600, LX800 Printers:	LX820, LX850 and HP Printers with 610 Inks:
 			 

All profiles are available for download at: www.fishertextiles.com/profiles.php

L25500 Printers

RIP: Onyx10

Load as: Fabric

Print Mode: 10 passes bidi

InkLimit: Normal

Drying temperature: 55°C

Curing temperature: 100°C

Airflow: 30%

OMAS: Enable

Cutter: Disable

Tension: 15N/m

Vaccum: 5mmH2O

WUDTO: 5°C

WUCTO: 0°C

CDDTO: 0°C

CDCTO: 0°C

Pmin: 1kW

RIP: Caldera

Load as: Fabric

Print Mode: 10 passes bidi

InkLimit: Normal

Drying temperature: 50°C

Curing temperature: 100°C

Airflow: 40%

OMAS: Enable

Cutter: Disable

Tension: 15N/m

Vaccum: 5mmH2O

WUDTO: 5°C

WUCTO: 0°C

CDDTO: 0°C

CDCTO: 0°C

Pmin: 1kW



L26500, L28500 Printers:

RIP: Onyx10

Load as: Fabric

Print Mode: 12 passes bidi

InkLimit: High

Drying temperature: 55°C

Curing temperature: 100°C

Airflow: 30%

OMAS: Enable

Cutter: Disable

Tension: 15N/m

Vaccum: 20mmH2O

WUDTO: 5°C

WUCTO: 0°C

CDDTO: 0°C

CDCTO: 0°C

Pmin: 0,7kW



L65500, LX600, LX800 Printers

RIP: Onyx

Load as: [Fabric] Polyester Fabric - 250%

Print Mode: 18 passes unidir

Input Tension: 75N/m

Output Tension: 60N/m

Vacuum: 15mmH2O

Airflow: 50%

Drying Temperature: 55°C

Curing Temperature: 95°C



LX820, LX850 and HP Printers with 610 Inks

RIP: Onyx and Caldera

Load as: [Fabric] Polyester Fabric - 250%

Print Mode: 10 passes bidi

Input Tension: 75N/m

Output Tension: 65N/m

Vacuum: 5mmH2O

Airflow: 50%

Drying Temperature: 55°C

Curing Temperature: 95°C

